~PORTABLE AIR CONDITIONER

ONLY COOLING

0,5W

0,5 W stand by

When room temperature reaches settings temperature power management control system will get unit running into low input standby mode.

Model NXP-25APO1-CA NXP -35APO1-CA Type only cooling Indoor unit power supply V/faza/Hz 220-240/1/50 Capacity rated kW 3,5 2,6 Rated power input W 1010 1350 Rated current Cooling А 4,4 5,9 EER W/W 2,6 2,6 Energy efficiency class А А 5,3/5,7/6,2 5,7/6,1/6,5 m³/min Airflow rate low/medium/high Sound pressure low/medium/high dB(A) 45/48/51 51/52/54 Internal fan Sound power at high speed dB(A) 65 65 Amount of condensate L/h 1,0 1,2 Туре R410A R410A Refrigerant GWP 2088 2088 Charge kg 0,44 0,42 Power consumption in stand-by mode W 0,5 0,5

Control			
Fuse	A	16	25
Recommended operation temperature range - ext. temp./int. temp.	°C	17-35/5-30	17-35/5-30
Recommended room size	m²	12-18	16-23
Dimensions (W x D x H)	mm	466x397x765	466x397x765
Shipping dimensions (W x D x H)	mm	515x443x880	515x443x880
Net/gross weight	kg	30,5/34,5	34,0/38,8