



EXTRA1250CD

Supermarket Multideck Cooler

Product features

- Can be multiplexed Create uninterupted continuous line
- Temperature Class 3M1
- Heavy duty shelving with strengthening bar
- Adjustable extra deep shelves to maximise capacity
- Tilting function for better product display
- Ticket strip and acrylic front riser as standard
- Internal vertical LED light
- Base plus 4 shelves
- Glass end walls as standard
- Multiplexing kit as accessory





Glass end walls as standard

Adjustable shelves with tilting function

Full Glass Door Multideck Cooler with Multiplexing Option

EXTRA Multideck is a full glass door quality cooler with double glazed hinged glass doors for added energy efficiency savings on running costs.

For greater stock capacity it has 460mm deep shelves to help maximise sales during busy periods and reduce restocking. It has excellent internal illumination with vertical LED lighting in each door and horizontally across the top on the 2500 model. Shelves can be flat or tilted to 10 or 20 degrees with ticket strips and shelf risers as standard.

It is suitable for display of packed fresh meat, dairy or drinks and is ideal for supermarkets, convenience stores, delis and sandwich shops where plug-in refrigeration is required.

Installation is simple and quick. No special requirements as refrigerant charge is below 150g.

The model allows for multiplexing and increases your possibilities to make the most of the space, you have available. The unit can be ordered without end walls and with a multiplexing kit if required.

Design and Material		
No. of Doors		2
Door No & Type		2 hinged glass doors
Door Reversible		No
No. of Shelves	pcs	4
Shelves No & Type	4 bla	ck sheet, tilting + base
Shelf Color		Black
Max Load of Shelves	kg/m²	100
Feet / Legs		4 adjustable feet
Castors		Option
Exterior Finish		Black / Glass

Measures and Co	ntent	
Temperature Range	°C	+2 to +6
Climate Class		3
Gross / Net Weight	kg	340 / 320
Gross / Net Volume	I	880 / 770
Total Display Area	m²	1,81
Cooling and Funct	tions	
Type of Controller		Electronic
Type of Cooling		Ventilated
Type of Defrost		Automatic, hot gas
Refrigerant		R290

Power and Consumption	
Energy Class	D
Energy Arrow	D A G

Energy Consumption	kWh/24h	11
Annual Energy Consumption	kWh/year	4015
Input Power	W	1100
Voltage / Frequency	V/Hz	220-
Noise Level	db(A)	53

TEFCOLD A/S - Industrivej 25 - 8800 Viborg - Denmark - Phone +45 86 60 19 33 - sales@tefcold.com - www.tefcold.com

Design and Material	
Interior Finish	Black
Interior Light	2 x Vertically LED
Lock	No

Refrigerant Charge	g	144
Thermometer		Yes
GWP		3

Power and Consumption

Dimensions

Internal Dimension (WxDxH)		1250 x 610 x 1399
	m	
External Dimension	m	1310 x 920 x 2035
(WxDxH)	m	
	m	1450 x 975 x 2230
	m	