## **BA26H**

## Backbar Cooler

## **Product Features**

- EU Energy Class A
- Approx. 59% more energy efficient than previous BA-range
- Ventilated cooling for fast pull-down and even temperature
- Energy saving variable speed compressor
- Double glazed tempered glass
- · Hinged alu-framed glass doors
- Easy access electronic thermostat
- · Adjustable shelves behind each door
- · LED interior light



276 188 143 143





Adjustable wire shelves

Electronic thermostat

## High-quality back bar with low energy consumption

The BA is our range of high-quality back bars. It has been updated and now uses in average 59% less energy compared to the previous models from the same range. This backbar has ventilated cooling for a short pull-down time to ensure that you can keep up with customer demand for cold beverages. If you need to adjust the temperature this is easily done on the electronic thermostat.

The back bar cooler is made of solid materials and has adjustable chrome shelves with closely-spaced wires, which gives you a high capacity and stability. Furthermore, it has hinged aluminium doors with double glazed tempered glass. This helps save energy, but it also means a great product visibility.

The BA range is also available in a variant with self-closing sliding doors.

Design and Material			
Door No & Type	2 hinged glass doors		
Door Reversible	No		
Tempered glass	Yes		
Shelves No & Type	4 wire shelves chrome		
Shelf Color	Chrome		
Shelf Dimensions	395x328 mm		
Feet / Legs	4 adjustable feet		
Exterior Finish	Black		
Interior Finish	Stucco aluminium		
Interior Light	LED		
Lock	Yes		

Measures and Content			
Total Display Area	m²	0.5	
Temperature Range	°C	+2 to +10	
Climate Class		4	
Gross / Net Weight	kg	69 / 63	
Gross / Net Volume	1	190 / 182	

Cooling and Functions			
Type of Controller		Electronic	
Type of Cooling		Ventilated	
Type of Defrost		Automatic	
Refrigerant		R600a	
Refrigerant Charge	g	70	
Thermometer		Yes	

Power and Consumption				
Energy Class		А		
Energy Consumption	kWh/24h	1.08		
Annual Energy Cons.	kWh/year	394		
Max Ambient		30°C at 55% RH		
Input Power	W	30°C at 55% RH 115		
max, morene	W V/Hz			
Input Power	••	115		

Dimensions		
Internal Dimension (WxDxH)	mm	900 x 418 x 720
External Dimension (WxDxH)	mm	900 x 520 x 870
Packed Dimension (WxDxH)	mm	985 x 575 x 940
40ft Container Load	pcs	96