

## EXTRA1875CD

### Supermarket Multideck Cooler



#### Product Features

- Can be multiplexed - Create uninterrupted continuous line
- Temperature Class 3M1
- Heavy duty shelving with strengthening bar
- Adjustable extra deep shelves to maximise capacity
- Tilting function for better product display
- Ticket strip and acrylic front riser as standard
- Internal vertical LED light
- Base plus 4 shelves
- Glass end walls as standard
- Multiplexing kit as accessory



Glass end walls as standard



60x40 cm boxes fit perfectly

### Full Glass Door Multideck Cooler with Multiplexing Option

EXTRA Multideck is a full glass door quality cooler with double glazed hinged glass doors for added energy efficiency savings on running costs.

For greater stock capacity it has 460mm deep shelves to help maximise sales during busy periods and reduce restocking. It has excellent internal illumination with vertical LED lighting in each door and horizontally across the top on the 2500 model. Shelves can be flat or tilted to 10 or 20 degrees with ticket strips and shelf risers as standard.

It is suitable for display of packed fresh meat, dairy or drinks and is ideal for supermarkets, convenience stores, delis and sandwich shops where plug-in refrigeration is required.

Installation is simple and quick. No special requirements as refrigerant charge is below 150g.

The model allows for multiplexing and increases your possibilities to make the most of the space, you have available. The unit can be ordered without end walls and with a multiplexing kit if required.

Design and Material			Measures and Content			Power and Consumption		
Door No & Type	3 hinged glass doors		Total Display Area	m <sup>2</sup>	2.72	Energy Class	C	
Tempered glass	Yes		Temperature Range	°C	+2 to +6	Energy Consumption	kWh/24h	14.03
Door Reversible	No		Climate Class	3		Annual Energy Cons.	kWh/year	5119
Shelves No & Type	4 black sheet, tilting + base		Gross / Net Weight	kg	475 / 425	Input Power	W	1300
Shelf Color	Black		Gross / Net Volume	l	1350 / 1160	Voltage / Frequency	V/Hz	220-240/50
Max load on Shelves	kg/m <sup>2</sup>	100				Noise Level	dB(A)	53
Feet / Legs			Cooling and Functions			Dimensions		
Feet / Legs	6 adjustable feet		Type of Controller	Electronic				
Castors	Option		Type of Cooling	Ventilated				
Exterior Finish	Black / Glass		Type of Defrost	Automatic, hot gas				
Interior Finish	Black		Refrigerant	R290				
						Internal Dimension	mm	1875 x 610 x 1399 (WxDxH)

**Design and Material**

Interior Light	2 x Vertically LED
Lock	No

**Measures and Content**

Refrigerant Charge	g	2x144
Thermometer		Yes

**Power and Consumption**

External Dimension (WxDxH)	mm	1975 x 920 x 2035
Packed Dimension (WxDxH)	mm	2075 x 975 x 2230
40ft Container Load	pcs	12