



EXTRA2500CD

Supermarket Multideck Cooler

Product Features

- Can be multiplexed Create uninterrupted continuous line
- Temperature Class 3M1
- Heavy duty shelving with strengthening bar
- · Adjustable extra deep shelves to maximise capacity
- Tilting function for better product display
- Ticket strip and acrylic front riser as standard
- Internal vertical LED light
- Base plus 4 shelves
- Glass end walls as standard
- Multiplexing kit as accessory





Glass end walls as standard

60x40 cm boxes fit perfectly

Full Glass Door Multideck Cooler with Multiplexing Option

EXTRA Multideck is a full glass door quality cooler with double glazed hinged glass doors for added energy efficiency savings on running costs.

For greater stock capacity it has 460mm deep shelves to help maximise sales during busy periods and reduce restocking. It has excellent internal illumination with vertical LED lighting in each door and horizontally across the top on the 2500 model. Shelves can be flat or tilted to 10 or 20 degrees with ticket strips and shelf risers as standard.

It is suitable for display of packed fresh meat, dairy or drinks and is ideal for supermarkets, convenience stores, delis and sandwich shops where plug-in refrigeration is required.

Installation is simple and quick. No special requirements as refrigerant charge is below 150g.

The model allows for multiplexing and increases your possibilities to make the most of the space, you have available. The unit can be ordered without end walls and with a multiplexing kit if required.

Design and Material Door No & Type 4 hinged glass doors Tempered glass Yes Door Reversible No Shelves No & Type 4 black sheet, tilting + base Shelf Color Black Max load on kg/m² 100 Shelves Feet / Legs 6 adjustable feet Castors Option Exterior Finish Black / Glass Interior Finish Black

Measures and Content			
Total Display Area	m²	3.63	
Temperature Range	°C	+2 to +6	
Climate Class		3	
Gross / Net Weight	kg	700 / 640	
Gross / Net Volume	I	1785 / 1540	
Cooling and Functions			
Type of Controller		Electronic	
Type of Cooling		Ventilated	
Type of Defrost		Automatic, hot gas	
Refrigerant		R290	

Power and Consumption			
Energy Class		C	
Energy Consumption	kWh/24h	15.75	
Annual Energy Cons.	kWh/year	5748	
Input Power	W	2200	
Voltage / Frequency	V/Hz	220-240/50	
Noise Level	dB(A)	53	

Dimensions		
Internal Dimension (WxDxH)	mm	2500 x 610 x 1399

TEFCOLD A/S - Industrivej 25 - 8800 Viborg - Denmark - Phone +45 86 60 19 33 - sales@tefcold.com - www.tefcold.com

Design and Material	
Interior Light	2 x Vertically LED
Lock	No

Measure	s and	Content
vicusuic	_s unu	CONCIN

Refrigerant Charge g

Thermometer

	Power and Consumption		
2x144	External Dimension	mm	2600 x 920 x 2035
Yes	(WxDxH)		
	Packed Dimension (WxDxH)	mm	2700 x 975 x 2230
	40ft Container Load	pcs	8