BA26S

Backbar Cooler

Product Features


- EU Energy Class A
- Approx. 59% more energy efficient than previous BA-range
- Double glazed tempered glass
- Energy saving variable speed compressor
- Self-closing sliding glass doors
- Ventilated cooling for fast pull-down and even temperature
- Easy access electronic thermostat
- Adjustable shelves behind each door
- · LED interior light
- Lock





Door holder for loading of the cabinet

Electronic thermostat



High-quality backbar with low energy consumption

The BA is our range of high-quality backbars. It has been updated and now uses in average 59% less energy compared to the previous models from the same range. This backbar has ventilated cooling for a short pull-down time to ensure that you can keep up with customer demand for cold beverages. If you need to adjust the temperature this is easily done on the electronic thermostat.

The backbar cooler is made of solid materials and has adjustable chrome shelves with closely-spaced wires, which gives you a high capacity and stability. Furthermore, it has self-closing aluminium sliding doors with double glazed tempered glass. This helps save energy, but it also means a great product visibility.

The BA range is also available in a variant with hinged doors.

Design and Material	
Door No & Type	2 sliding glass doors
Door Reversible	No
Tempered glass	Yes
Shelves No & Type	4 wire shelves chrome
Shelf Color	Chrome
Shelf Dimensions	395x328 mm
Feet / Legs	4 adjustable feet
Exterior Finish	Black
Interior Finish	Stucco aluminium
Interior Light	LED
Lock	Yes

Measures and Content			
Total Display Area	m²	0.52	
Temperature Range	°C	+2 to +10	
Climate Class		4	
Gross / Net Weight	kg	69 / 63	
Gross / Net Volume	-1	190 / 182	

Cooling and Functions			
Type of Controller		Electronic	
Type of Cooling		Ventilated	
Type of Defrost		Automatic	
Refrigerant		R600a	
Refrigerant Charge	g	70	
Thermometer		Yes	

Power and Consumption				
Energy Class		А		
Energy Consumption	kWh/24h	1.14		
Annual Energy Cons.	kWh/year	416		
Max Ambient		30°C at 55% RH		
Max Ambient Input Power	W	30°C at 55% RH 115		
THE STATE OF THE S	W V/Hz			
Input Power	••	115		

Dimensions		
Internal Dimension (WxDxH)	mm	810 x 418 x 720
External Dimension (WxDxH)	mm	900 x 515 x 870
Packed Dimension (WxDxH)	mm	985 x 575 x 940
40ft Container Load	pcs	96