



PC1250B

Supermarket Multideck Cooler

Product Features

- Frameless glass doors for great product visibility
- Low energy consumption
- Black interior and exterior
- Adjustable shelves with tilting function
- LED light under each shelf
- Ventilated cooling for fast pull-down and even temperature
- Digital controller and temperature display
- Glass end walls as standard
- Castors and locking feet
- 33 mm ticket strips with shelf risers included





for each feature

Display with a button LED light under each shelf

Black multideck cooler with frameless glass doors

The PC multideck cooler is all about product visibility and comes with frameless glass doors as well as glass end walls. To further highlight the products, the cooler is equipped with horizontal LED lighting at the top of the cabinet and below each shelf. The 450 mm deep shelves are adjustable and have a tilting function for better product presentation. Front risers are included.

The PC is a spacious cooler with a low energy consumption, and you get a good quality for a competitive price. It is temperature class 3M1, which means it is suitable for display of packed fresh meat, dairy products, fresh fruit and vegetables and is ideal for supermarkets, convenience stores, delis or sandwich shops.

Design and Material					
Door No & Type		2 hinged glass doors			
Tempered glass		Yes			
Shelves No & Type		5 adjustable			
Shelf Color		Black			
Max load on Shelves	kg/m²	160			
Feet / Legs		4 adjustable feet			
Castors		4 castors			
Exterior Finish		Black RAL9005			
Interior Finish		Black RAL9005			
Interior Light		LED			

Measures and Content				
m²	3.14			
°C	-1 to +5			
	3			
kg	300 / 260			
I	1292 / 764			
	m² °C			

Cooling and Functions				
Type of Controller		Electronic		
Type of Cooling		Ventilated		
Type of Defrost		Automatic		
Refrigerant		R290		
Refrigerant Charge	g	149		
Thermometer		Yes		

Power and Consur	Power and Consumption				
Energy Class		В			
Energy Consumption	kWh/24h	5.87			
Annual Energy Cons.	kWh/year	2143			
Input Power	W	550			
Voltage / Frequency	V/Hz	220-240/50			
Noise Level	dB(A)	62			

	Dimensions				
	Internal Dimension (WxDxH)	mm	1250 x 450 x 1540		
	External Dimension (WxDxH)	mm	1310 x 740 x 2050		
	Packed Dimension (WxDxH)	mm	1340 x 770 x 2120		
	40ft Container Load	pcs	25		