

PC2500B

Supermarket Multideck Cooler

Product Features

- Frameless glass doors for great product visibility
- Low energy consumption
- Black interior and exterior
- Adjustable shelves with tilting function
- · LED light under each shelf
- Ventilated cooling for fast pull-down and even temperature
- Digital controller and temperature display
- · Glass end walls as standard
- 33 mm ticket strips with shelf risers included
- Castors and locking feet





for each feature

Display with a button LED light under each shelf

Black multideck cooler with frameless glass doors

The PC multideck cooler is all about product visibility and comes with frameless glass doors as well as glass end walls. To further highlight the products, the cooler is equipped with horizontal LED lighting at the top of the cabinet and below each shelf. The 450 mm deep shelves are adjustable and have a tilting function for better product presentation. Front risers are included.

The PC is a spacious cooler with a low energy consumption, and you get a good quality for a competitive price. It is temperature class 3M1, which means it is suitable for display of packed fresh meat, dairy products, fresh fruit and vegetables and is ideal for supermarkets, convenience stores, delis or sandwich shops.

Design and Material			
Door No & Type	4 hinged glass doors		
Tempered glass	Yes		
Shelves No & Type	5 adjustable		
Shelf Color	Black		
Max load on k Shelves	g/m² 160		
Feet / Legs	6 adjustable feet		
Castors	6 castors		
Exterior Finish	Black RAL9005		
Interior Finish	Black RAL9005		
Interior Light	LED		

Measures and Content				
Total Display Area	m²	5.13		
Temperature Range	°C	-1 to +5		
Climate Class		3		
Gross / Net Weight	kg	500 / 440		
Gross / Net Volume	I	2585 / 1529		

Cooling and Functions				
Type of Controller		Electronic		
Type of Cooling		Ventilated		
Type of Defrost		Automatic		
Refrigerant		R290		
Refrigerant Charge	g	2 x 149		
Thermometer		Yes		

Power and Consumption				
Energy Class		В		
Energy Consumption	kWh/24h	10.2		
Annual Energy Cons.	kWh/year	3723		
Input Power	W	1060		
Voltage / Frequency	V/Hz	220-240/50		
Noise Level	dB(A)	65		

Dimensions		
Internal Dimension (WxDxH)	mm	2500 x 450 x 1540
External Dimension (WxDxH)	mm	2560 x 740 x 2050
Packed Dimension (WxDxH)	mm	2590 x 770 x 2120
40ft Container Load	pcs	12