BA31S-3

Backbar Cooler

Product Features


- EU Energy Class B
- Approx. 59% more energy efficient than previous BA-range
- Double glazed tempered glass
- Energy saving variable speed compressor
- Self-closing sliding glass doors
- Ventilated cooling for fast pull-down and even temperature
- Easy access electronic thermostat
- Adjustable shelves behind each door
- LED interior light
- Lock





Door holder for loading of the cabinet

Electronic thermostat



High-quality backbar with low energy consumption

The BA is our range of high-quality backbars. It has been updated and now uses in average 59% less energy compared to the previous models from the same range. This backbar has ventilated cooling for a short pull-down time to ensure that you can keep up with customer demand for cold beverages. If you need to adjust the temperature this is easily done on the electronic thermostat.

The backbar cooler is made of solid materials and has adjustable chrome shelves with closely-spaced wires, which gives you a high capacity and stability. Furthermore, it has self-closing aluminium sliding doors with double glazed tempered glass. This helps save energy, but it also means a great product visibility.

The BA range is also available in a variant with hinged doors.

Design and Material		
Door No & Type	3 sliding glass doors	
Door Reversible	No	
Tempered glass	Yes	
Shelves No & Type	6 wire shelves chrome	
Shelf Color	Chrome	
Shelf Dimensions	400x318 / 432x318 mm	
Feet / Legs	4 adjustable feet	
Exterior Finish	Black	
Interior Finish	Stucco aluminium	
Interior Light	LED	
Lock	Yes	

Measures and Content				
0.84				
+2 to +10				
4				
101 / 94				
311 / 288				

Cooling and Functions				
Type of Controller		Electronic		
Type of Cooling		Ventilated		
Type of Defrost		Automatic		
Refrigerant		R290		
Refrigerant Charge	g	90		
Thermometer		Yes		

Power and Consumption				
Energy Class		В		
Energy Consumption	kWh/24h	1.74		
Annual Energy Cons.	kWh/year	635		
Power		1		
Max Ambient		30°C at 55% RH		
Input Power	W	125		
Voltage / Frequency	V/Hz	220-240/50		
Noise Level	dB(A)	44		

Dimensions		
Internal Dimension (WxDxH)	mm	1265 x 418 x 734
External Dimension (WxDxH)	mm	1350 x 515 x 900
Packed Dimension (WxDxH)	mm	1435 x 575 x 970

Power and Consumption

40ft Container Load

ncs

64

TEFCOLD A/S - Industrivej 25 - 8800 Viborg - Denmark - Phone +45 86 60 19 33 - sales@tefcold.com - www.tefcold.com