

## TM35GC

### Glass Door Minibar Cooler

#### Product Features

- Compressor operated cooling system
- Great product presentation
- Low energy consumption
- Low noise operation
- Timing function for maximum guest comfort
- SLEEP-mode function for silence period
- FAST-cool function for immediate cooling
- Reversible glass door
- LED interior light
- Integrated handle
- Lock



Wire shelves available  
as option



Glass shelves available  
as option

### Minibar with glass door for great product presentation

This compressor operated minibar with a glass door is an excellent choice for hotels in warmer surroundings. The cooling system helps secure a lower temperature level as well as a shorter pull-down time compared to absorption operated minibars.

It also has some cool programming features. It can be timed, so the compressor only runs when the room is highly likely to be empty, e.g. from 9-12 am and 6-9 pm. This means it is completely silent at other times, when guests are likely to be in the room. A so-called water-pack maintains the cold temperature in the minibar, when it is not running. It also features a SLEEP-mode for forced silence as well as a FAST-cool function for immediate cooling. This is very handy if guests arrive at an odd hour.

The minibar is designed to be elegantly discreet with a black exterior. The glass door provides excellent product presentation, so guests can be tempted by a nice display of cold beverages and delicious snacks.

Design and Material		Measures and Content		Power and Consumption	
Door No & Type	1 hinged glass door	Temperature Range	°C +5 to +14	Energy Class	G
Door Reversible	Yes	Climate Class	4	Energy Consumption	kWh/24h 0.31
Shelves No & Type	1 plastic shelf	Gross / Net Weight	kg 24 / 23	Annual Energy Cons.	kWh/year 113
Feet / Legs	Adjustable feet	Gross / Net Volume	l 27 / 24	Input Power	W 65
Exterior Finish	Black	<b>Cooling and Functions</b>		Voltage / Frequency	V/Hz 220-240/50
Interior Finish	White			Noise Level	dB(A) 38
Interior Light	LED			<b>Dimensions</b>	
Lock	Yes			Type of Controller	Electronic
		Type of Cooling	Static	External Dimension	mm 402 x 425 x 505 (WxDxH)
		Type of Defrost	Automatic	Packed Dimension	mm 450 x 475 x 550 (WxDxH)
		Refrigerant	R600a		
		Refrigerant Charge	g 24		
		Thermometer	No		

