

## TM45C

### Minibar Cooler

#### Product Features

- Low energy consumption
- Compressor operated cooling system
- Low noise operation
- Timing function for maximum guest comfort
- SLEEP-mode function for silence period
- FAST-cool function for immediate cooling
- Adjustable shelves, also in door
- Reversible solid door
- LED interior light
- Integrated handle
- Lock



Integrated handle



Lock

### Minibar cooler with an exceptional low energy consumption

This compressor operated minibar with a solid door is an excellent choice for hotels in warmer surroundings. The cooling system helps secure a lower temperature level as well as a shorter pull-down time compared to absorption operated minibars.

It also has some cool programming features. It can be timed, so the compressor only runs when the room is highly likely to be empty, e.g. from 9-12 am and 6-9 pm. This means it is completely silent at other times, when guests are likely in the room. A so-called water-pack maintains the cold temperature in the minibar, when it is running. It also features a SLEEP-mode for forced silence as well as a FAST-cool function for immediate cooling. This is very handy if guests arrive at an odd hour.

The minibar is designed to be elegantly discreet with a black exterior. It can also be fully built in with a build-in bracket and hinge fixation kit, which allows a joint opening of the cupboard- and minibar door. A hinge fixation kit also secures the stability of the cooler and prevents it from tipping and sliding forward.

Design and Material		Measures and Content		Power and Consumption		
Door No & Type	1 hinged solid door	Temperature Range	°C	+5 to +10	Energy Class	D
Door Reversible	Yes	Climate Class		4	Energy Consumption	kWh/24h 0.16
Shelves No & Type	2 plastic shelves	Gross / Net Weight	kg	21 / 20	Annual Energy Cons.	kWh/year 57
Feet / Legs	Adjustable feet	Gross / Net Volume	l	38 / 34	Power	1
Exterior Finish	Black	<b>Cooling and Functions</b>			Max Ambient	30°C at 55% RH
Interior Finish	White	Type of Controller		Electronic	Input Power	W 65
Interior Light	LED	Type of Cooling		Static	Voltage / Frequency	V/Hz 220-240/50
Lock	Yes	Type of Defrost		Automatic	Noise Level	dB(A) 38
		Refrigerant		R600a	<b>Dimensions</b>	
		Refrigerant Charge	g	26	Internal Dimension	mm 310 x 300 x 455 (WxDxH)
		Thermometer		No		

## Power and Consumption

External Dimension (WxDxH)	mm	402 x 500 x 565
Packed Dimension (WxDxH)	mm	450 x 535 x 620
40ft Container Load	pcs	330