## TM45GC

Glass Door Minibar Cooler

## **Product Features**

- Compressor operated cooling system
- Great product presentation
- Low energy consumption
- Low noise operation
- Timing function for maximum guest comfort
- SLEEP-mode function for silence period
- FAST-cool function for immediate cooling
- Reversible glass door
- LED interior light
- Integrated handle
- Lock







Display with a button for each feature

## Minibar with glass door for great product presentation

This compressor operated minibar with a glass door is an excellent choice for hotels in warmer surroundings. The cooling system helps secure a lower temperature level as well as a shorter pull-down time compared to absorption operated minibars.

It also has some cool programming features. It can be timed, so the compressor only runs when the room is highly likely to be empty, e.g. from 9-12 am and 6-9 pm. This means it is completely silent at other times, when guests are likely to be in the room. A so-called water-pack maintains the cold temperature in the minibar, when it is not running. It also features a SLEEP-mode for forced silence as well as a FAST-cool function for immediate cooling. This is very handy if guests arrive at an odd hour.

The minibar is designed to be elegantly discreet with a black exterior. The glass door provides excellent product presentation, so guests can be tempted by a nice display of cold beverages and delicious snacks.

Design and Material	
Door No & Type	1 hinged glass door
Door Reversible	Yes
Shelves No & Type	2 plastic shelves
Feet / Legs	Adjustable feet
Exterior Finish	Black
Interior Finish	White
Interior Light	LED
Lock	Yes

Measures and Content				
Temperature Range	°C	+5 to +14		
Climate Class		4		
Gross / Net Weight	kg	26 / 24		
Gross / Net Volume	I	38 / 34		

Cooling and Functions		
Type of Controller	Electronic	
Type of Cooling	Static	
Type of Defrost	Automatic	
Refrigerant	R600a	
Refrigerant Charge g	26	
Thermometer	No	

Power and Consumption				
Energy Class		G		
Energy Consumption	kWh/24h	0.35		
Annual Energy Cons.	kWh/year	128		
Input Power	W	65		
Voltage / Frequency	V/Hz	220-240/50		
Noise Level	dB(A)	38		

Dimensions		
Internal Dimension (WxDxH)	mm	310 x 300 x 455
External Dimension (WxDxH)	mm	402 x 485 x 565
Packed Dimension (WxDxH)	mm	450 x 535 x 620

Power and Consumption

40ft Container Load

ncs

330