



LCT750C/BLACK

Refrigerated Display Counter

Product Features

- Stainless steel
- Double glazed glass
- Rear glass sliding doors
- Adjustable feet
- Curved top/glass top/front
- LED interior light
- Ventilated cooling

Tabletop display counter for great product presentation

This refrigerated display case with a curved glass front offers high quality with a stainless steel finish and double glazed glass. The small size makes it ideal for placing on a countertop to tempt customers with a display of pastries. It has glass sliding doors to the rear, providing easy access to the content. The counter comes with fixed wire shelves and LED lighting for optimal product presentation.

| Measures and Content | | |
|----------------------------|----------|------------------------------|
| Total Display Area | m² | 0.7 |
| Temperature Range | °C | +2 to +8 |
| Climate Class | | 3 |
| Gross / Net Weight | kg | 87 / 63 |
| Gross / Net Volume | 1 | 100 / 60 |
| Design and Material | | |
| Door No & Type | | 2 sliding glass doors |
| Tempered glass | | Yes |
| Shelves No & Type | | 2 wire shelves chrome + base |
| Feet / Legs | | 4 adjustable feet |
| Exterior Finish | | Stainless steel / Glass |
| Interior Finish | | Stainless steel / Glass |
| Interior Light | | LED |
| Cooling and Functions | | |
| Type of Controller | _ | Electronic |
| Type of Cooling | | Ventilated |
| Type of Defrost | | Automatic |
| Refrigerant | | R290 |
| Refrigerant Charge | g | 45 |
| Thermometer | | Yes |
| Power and Consumption | | |
| Energy Class | | С |
| Energy Consumption | kWh/24h | 4.13 |
| Annual Energy Cons. | kWh/year | 1507 |
| Input Power | W | 242 |
| Voltage / Frequency | V/Hz | 220-240/50 |
| Noise Level | dB(A) | 48 |
| Dimensions | | |
| Internal Dimension (WxDxH) | mm | 640 x 450 x 400 |
| External Dimension (WxDxH) | mm | 700 x 560 x 670 |
| Packed Dimension (WxDxH) | mm | 784 x 641 x 790 |
| 40ft Container Load | pcs | 153 |
| | | |





Pastry display

Sliding doors