



EXTRA1250FD

Supermarket Multideck Freezer

Product Features

- Can be multiplexed Create uninterrupted continuous line
- Temperature Class 3L1
- · Heavy duty shelving with strengthening bar
- · Adjustable extra deep shelves to maximise capacity
- Internal vertical LED light
- Base plus 4 shelves
- · Solid end walls as standard
- Multiplexing kit as accessory

Full Class Door Multideck Freezer with Multiplexing Opti

EXTRA Multideck is a premium full glass door freezer with double glazed hinged glass doors for added energy efficiency savings on running costs. For greater stock capacity it has 460mm deep shelves to help maximise sales during busy periods and reduce restocking. It has excellent internal illumination with vertical LED lighting in each door and horizontally across the top on the 2500 model. Wire shelving with ticket strips and shelf risers are supplied as standard. Installation is simple and quick. No special requirements as refrigerant charge is below 150g. The model allows for multiplexing and increases your possibilities to make the most of the space, you have available. The unit can be ordered without end walls and with a multiplexing kit if required.

Measures and Content		
Total Display Area	m²	1.53
Temperature Range	°C	-21 to -18
Climate Class		3
Gross / Net Weight	kg	350 / 330
Gross / Net Volume	1	880 / 850
Design and Material		
Door No & Type		2 hinged glass doors
Tempered glass		Yes
Door Reversible		No
Shelves No & Type		8 wire shelves black
Shelf Color		Black
Max load on Shelves	kg/m²	150
Feet / Legs		4 adjustable feet
Castors		Option
Exterior Finish		Black / Glass
Interior Finish		Black
Interior Light		2 x Vertically LED
Lock		No
Cooling and Functions		
Type of Controller		Electronic
Town of Cooling		V

200.1		110
Cooling and Functions		
Type of Controller		Electronic
Type of Cooling		Ventilated
Type of Defrost		Automatic, hot gas
Refrigerant		R290
Refrigerant Charge	g	149
Thermometer		Yes
Power and Consumption		
Energy Class		D
Energy Consumption	kWh/24h	15.28
Annual Energy Cons.	kWh/year	5578
Input Power	W	1100
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	53
Dimensions		
Internal Dimension (WxDxH)	mm	1250 x 610 x 1399
External Dimension (WxDxH)	mm	1350 x 930 x 2035
Packed Dimension (WxDxH)	mm	1450 x 975 x 2230
40ft Container Load	pcs	16





Extraordinary space on Electronic thermostat shelves