



Galaxy+ GP26FGD Black

Supermarket Multideck Cooler

Product Features

- EU Energy Class B
- · Can be multiplexed Create uninterrupted continuous line
- Frameless glass doors for great product visibility
- Adjustable shelves with tilting function
- Heavy duty shelving with strengthening bar
- Ticket strip and acrylic front riser as standard
- Self-closing doors
- Stainless steel bumper bars
- Ventilated cooling
- Multiplexing kit as accessory
- Solid 40 mm endwalls with mirrored interior

Energy efficient multideck cooler with doors

With this full glass door multideck cooler, you get a gorgeous design combined with an energy efficient cooling system. The frameless full vision glass doors allow for great visibility of the products inside. Vertical LED lights run down the inside of each wall, which combined with horizontal LED lighting across the top give excellent illumination and make the contents stand out. The cabinet comes with 5 shelves (plus base), to maximize storage and display space. The shelves can be tilted to optimize product presentation. Multiplexing kits are available as accessories, so you can create uninterrupted lines throughout your store. As a result of a carefully designed refrigeration system and optimal airflow through the cooler, this cabinet has an outstanding low energy consumption and an impressive EU energy rating.

Total Display Aream²3.83Temperature Range°C-1 to +5Climate Class3Gross / Net Weightkg490 / 459Gross / Net VolumeI2887 / 1258Design and MaterialVDoor No & Type4 hinged glass doorsTempered glassYesDoor ReversibleNoShelves No & Type5 adjustableShelves No & Type5 adjustableShelf ColorBlackShelf ColorBlackShelf Dimensions1250x400mmMax load on Shelveskg/m²Ketrior FinishBlack RAL9005Interior LightLEDLockNoCooling and FunctionsYesType of ControllerElectronicType of ControllerYesPower and ConsumptionKWh/24hFergy ConsumptionkWh/24hAnnual Energy Cons.kWh/24hIntery ConsumptionKWh/24hNoise LeveldB(A)Oklage / FrequencyV/HzVoltage / FrequencyW/Hz <t< th=""><th>Measures and Content</th><th></th><th></th></t<>	Measures and Content		
Climate Class 3 Gross / Net Weight kg 490 / 459 Gross / Net Volume 1 2887 / 1258 Design and Material 2 2 Door No & Type 4 hinged glass doors Yes Door Ro & Type 5 adjustable No Shelves No & Type 5 adjustable Self Color Shelf Color Black Shelf Color Black Shelf Color Black Self Color Black Shelf Color Black RAL9005 Interior Black RAL9005 Interior Finish Black RAL9005 Interior Finish Black RAL9005 Interior Finish Black RAL9005 No Cooling and Functions Ventilated No Type of Controller Electronic No Cooling and Functions Refrigerant Re290 Refrigerant Charge g 2x150 Thermometer Yes Power and Consumption KWh/24h 7.73 Annual Energy Consumption kWh/24h 7.73 Annual Energy Consumption <	Total Display Area	m ²	3.83
Gross / Net Weightkg490 / 450Gross / Net Volume12887 / 1258Design and Material2887 / 1258Door No & Type4 hinged glass doorsTempered glassYesDoor ReversibleNoShelves No & Type5 adjustableShelf ColorBlackShelf ColorBlackShelf Dimensions1250x400mmMax load on Shelveskg/m²Shelf DimensionsBlack RAL9005Interior FinishBlack RAL9005Interior FinishBlack RAL9005Interior FinishBlack RAL9005Interior FinishBlack RAL9005Interior ColingVentilatedType of ControllerElectronicType of ControllerRefrigerantRefrigerantR290Refrigerant ChargegPower and ConsumptionKWh/24hEnergy ClassBMax Ambient25°C at 60% RHEnergy ConsumptionKWh/yearPowerWNo868Voltage / FrequencyV/HzVHz220-240/50Noise LevelB(A)Dimension (WxDxH)mmPacked Dimension (WxDxH)mm	Temperature Range	°C	-1 to +5
Gross / Net VolumeI2887 / 1258Design and MaterialI2887 / 1258Door No & Type4 hinged glass doorsTempered glassYesDoor ReversibleNoShelves No & Type5 adjustableShelf ColorBlackShelf Dimensions1250x400mmMax load on Shelveskg/m²Kg/m²6 adjustable feetExterior FinishBlack RAL9005Interior FinishBlack RAL9005Interior LightLEDLockNoCooling and FunctionsElectronicType of ControllerElectronicType of ControllerSteff ageType of ControllerSteff ageType of ControllerYesPower and ConsumptionKWh/24hEnergy ClassBMax Ambient25°C at 60% RHEnergy ConsumptionKWh/yearInput PowerWVoltage / FrequencyV/HzVoltage / FrequencyV/HzVoltage / FrequencyW/HzNoise LeveldB(A)Dimension (WxDxH)mmPacked Dimension (WxDxH)mmSteff So x 770 x 230Steff So x 770 x 230Steff So x 770 x 230Steff So X 700 x 240Stef	Climate Class		3
Design and MaterialDoor No & Type4 hinged glass doorsTempered glassYesDoor ReversibleNoShelves No & Type5 adjustableShelf ColorBlackShelf Dimensions1250x400mmMax load on Shelveskg/m²Kg/m²6 adjustable feetExterior FinishBlack RAL9005Interior FinishBlack RAL9005Interior LightLEDLockNoCooling and FunctionsElectronicType of ControllerElectronicType of ControllerR290RefrigerantR290Refrigerant ChargegPower and ConsumptionKWh/24hEnergy ClassBMax Ambient25°C at 60% RHEnergy ConsumptionKWh/yearInput PowerWNoise LeveldB(A)Otage / FrequencyV/HzNoise LeveldB(A)Dimensions5DimensionsFired AutomaticRefrigerant Dimension (WxDxH)mmAnnual Energy ConsumptionKWh/24hNoise LeveldB(A)Staternal Dimension (WxDxH)mmAnnual Energy ConsumptionKYDA2ARefrigerant Dimension (WxDxH)mmAnnual Energy ConsumptionKYDA2AStaternal Dimension (WxDxH)mmStaternal Dimension (WxDxH)mmStaternal Dimension (WxDxH)mmStaternal Dimension (WxDxH)mmStaternal Dimension (WxDxH)Staternal Dimension (WxDxH)<	Gross / Net Weight	kg	490 / 459
Door No & Type4 hinged glass doorsTempered glassYesDoor ReversibleNoShelves No & Type5 adjustableShelr ColorBlackShelf ColorBlackShelf ColorBlackShelf Dimensions1250x400mmMax load on Shelveskg/m²Kg/m²6 adjustable feetExterior FinishBlack RAL9005Interior FinishBlack RAL9005Interior LightLEDLockNoCooling and FunctionsVentilatedType of ControllerElectronicType of ControllerRefragerantRefrigerantR290Refrigerant ChargegPower and ConsumptionKWh/24hEnergy ClassBMax Ambient25°C at 60% RHEnergy ConsumptionkWh/24hInput PowerWKoltage / FrequencyV/Hz200x 544 x 1562DimensionsMaxNoise LeveldB(A)Dise LevelMaxNoise LevelMaxSheff ColingState SSheff ColonsSDimension (WxDxH)mm2500 x 544 x 1562External Dimension (WxDxH)mmPacked Dimension (WxDxH)mmPacked Dimension (WxDxH)mmState of SSSon x 700 x 2320SSon x 700 x 2400S </td <td>Gross / Net Volume</td> <td>1</td> <td>2887 / 1258</td>	Gross / Net Volume	1	2887 / 1258
Tempered glass Yes Door Reversible No Shelves No & Type 5 adjustable Shelf Color Black Shelf Dimensions 1250x400mm Max load on Shelves kg/m² 160 Feet / Legs 6 adjustable feet Exterior Finish Black RAL9005 Interior Finish Black RAL9005 Interior Light LED Lock No Cooling and Functions Slett Conic Type of Controller Electronic Type of Cooling Ventilated Type of Cooling Ventilated Type of Defrost Automatic Refrigerant Charge g 2x150 Thermometer Yes Power and Consumption KWh/24h 7.73 Innual Energy Cons. kWh/24h 7.73 Annual Energy Cons. kWh/year 2802 Power M6 (A) 55 Dimensions KWh/year 2812 Power KM/A 55 Dinensions KWh/24h 55 Dimension (WxDxH)	Design and Material		
Door ReversibleNoShelves No & Type5 adjustableShelf ColorBlackShelf ColorBlackShelf Dimensions1250x400mmMax load on Shelveskg/m²Kagma?160Feet / Legs6 adjustable feetExterior FinishBlack RAL9005Interior FinishBlack RAL9005Interior LightLEDLockNoCooling and FunctionsElectronicType of ControllerElectronicType of ControllerElectronicType of ControllerRefrigerantRefrigerantR290Refrigerant ChargegPower and ConsumptionYesPower and ConsumptionKWh/24hEnergy ClassBMax Ambient25°C at 60% RHEnergy ConsumptionkWh/24hInterior SimptionKWh/24hIntering PrequencyV/Hz220-240/50Noise LevelMoise LeveldB(A)Dimension (WxDxH)mmPacked Dimension (WxDxH) <td>Door No & Type</td> <td></td> <td>4 hinged glass doors</td>	Door No & Type		4 hinged glass doors
Shelves No & Type 5 adjustable Shelf Color Black Shelf Color Black Shelf Dimensions 1250x400mm Max load on Shelves kg/m² 160 Feet / Legs 6 adjustable feet Exterior Finish Black RAL9005 Interior Finish Black RAL9005 Interior Finish Black RAL9005 Interior Light LED Lock No Cooling and Functions Ventilated Type of Controller Electronic Type of Controller Ventilated Type of Controller Refrigerant Refrigerant Charge g 2x150 Thermometer Yes Power and Consumption KWh/24h 7.73 Annual Energy Consumption kWh/24h 7.73 Innual Energy Cons. kWh/year 2821 Power Me 868 Voltage / Frequency V/Hz 220-240/50 Noise Level dB(A) 55 Dimension (WxDxH) mm 2580 x 740 x 2040 Packed Dimension (WxDxH) mm	Tempered glass		Yes
Shelf ColorBlackShelf Dimensions1250x400mmMax load on Shelveskg/m²160Feet / Legs6 adjustable feetExterior FinishBlack RAL9005Interior FinishBlack RAL9005Interior LightLEDLockNoCooling and FunctionsElectronicType of ControllerElectronicType of CoolingVentilatedType of DefrostAutomaticRefrigerantR290Refrigerant ChargegPower and ConsumptionYesEnergy ClassBMax Ambient25°C at 60% RHEnergy ConsumptionkWh/yearPower16 AmpInput PowerWKoltage / FrequencyV/HzV/Hz220-240/50Noise LeveldB(A)Dimension (WxDxH)mmPacked Dimension (WxDxH)	Door Reversible		No
Shelf Dimensions 1250x400mm Max load on Shelves kg/m² 160 Feet / Legs 6 adjustable feet Exterior Finish Black RAL9005 Interior Finish Black RAL9005 Interior Light LED Lock No Cooling and Functions No Type of Controller Electronic Type of Cooling Ventilated Type of Cooling Ventilated Type of Defrost Automatic Refrigerant R290 Refrigerant Charge g 2x150 Thermometer Yes Power and Consumption KWh/24h 7.73 Annual Energy Cons. kWh/year 2821 Power 16 Amp 100 Amp Input Power W 868 Voltage / Frequency V/Hz 220-240/50 Noise Level dE(A) 55 Dimensions Mm 2500 x 544 x 1562 External Dimension (WxDxH) mm 2500 x 544 x 2040 Packed Dimension (WxDxH) mm 2500 x 540 x 2040	Shelves No & Type		5 adjustable
Max load on Shelveskg/m²160Feet / Legs6 adjustable feetExterior FinishBlack RAL9005Interior FinishBlack RAL9005Interior LightLEDLockNoCooling and FunctionsNoType of ControllerElectronicType of CoolingVentilatedType of CoolingVentilatedType of DefrostAutomaticRefrigerantR290Refrigerant ChargegPower and ConsumptionYesEnergy ClassBMax Ambient25°C at 60% RHEnergy ConsumptionkWh/24hPower16 AmpInput PowerWKWh/year2821Power6 AmpInput PowerWKWh/year2820DinensionsSDimension (WxDxH)mmPacked Dimension (W	Shelf Color		Black
Feet / Legs6 adjustable feetExterior FinishBlack RAL9005Interior FinishBlack RAL9005Interior LightLEDLockNoCooling and FunctionsNoType of ControllerElectronicType of CoolingVentilatedType of DefrostAutomaticRefrigerantR290Refrigerant ChargegPower and ConsumptionYesEnergy ClassBMax Ambient25°C at 60% RHEnergy ConsumptionkWh/24hPower16 AmpInput PowerWRofer / FrequencyV/HzVoltage / FrequencyV/HzSoise LeveldB(A)Dimension (WxDxH)mmPacked Dimension (WxDxH)Packed Dimension (WxDxH) <td>Shelf Dimensions</td> <td></td> <td>1250x400mm</td>	Shelf Dimensions		1250x400mm
Exterior FinishBlack RAL9005Interior FinishBlack RAL9005Interior LightLEDLockNoCooling and FunctionsType of ControllerElectronicType of CoolingVentilatedType of DefrostAutomaticRefrigerant ChargegRefrigerant ChargegPower and ConsumptionYentilatedEnergy ClassBMax Ambient25°C at 60% RHEnergy ConsumptionkWh/24hPower16 AmpInput PowerWSolage / FrequencyV/HzVoltage / FrequencyV/HzDimension (WxDxH)mmPacked Dimension (WxDxH)Packed Dimension (WxDxH)<	Max load on Shelves	kg/m²	160
Interior Finish Black RAL9005 Interior Light LED Lock No Cooling and Functions Type of Controller Electronic Type of Cooling Ventilated Type of Defrost Automatic Refrigerant Charge g 2x150 Thermometer Yes Power and Consumption Energy Class B Max Ambient 25°C at 60% RH Energy Consumption kWh/24h 7.73 Annual Energy Cons. kWh/year 2821 Power 16 Amp Input Power W 868 Voltage / Frequency V/Hz 220-240/50 Noise Level dB(A) 55 Dimensions Internal Dimension (WxDxH) mm 2500 x 544 x 1562 External Dimension (WxDxH) mm 2580 x 740 x 2040 Packed Dimension (WxDxH) mm 2580 x 740 x 2040	Feet / Legs		6 adjustable feet
Interior Light LED Lock No Cooling and Functions Type of Controller Electronic Type of Cooling Ventilated Type of Defrost Automatic Refrigerant Charge g 2x150 Thermometer Yes Power and Consumption Energy Class B Max Ambient 25°C at 60% RH Energy Consumption kWh/24h 7.73 Annual Energy Cons. kWh/year 2821 Power 16 Amp Input Power W 8688 Voltage / Frequency V/Hz 220-240/50 Noise Level dB(A) 55 Dimensions Internal Dimension (WxDxH) mm 2500 x 544 x 1562 External Dimension (WxDxH) mm 2580 x 740 x 2040 Packed Dimension (WxD	Exterior Finish		Black RAL9005
Lock No Cooling and Functions Type of Controller Electronic Type of Cooling Ventilated Type of Defrost Automatic Refrigerant Charge g 2x150 Thermometer Yes Power and Consumption Energy Class B Max Ambient 25°C at 60% RH Energy Consumption kWh/24h 7.73 Annual Energy Cons. kWh/year 2821 Power 16 Amp Input Power W 868 Voltage / Frequency V/Hz 220-240/50 Noise Level dB(A) 55 Dimensions Internal Dimension (WxDxH) mm 2500 x 544 x 1562 External Dimension (WxDxH) mm 2580 x 740 x 2040 Packed Dimension (WxDxH) mm 2580 x 740 x 2040 Packed Dimension (WxDxH) mm 2580 x 740 x 2040	Interior Finish		Black RAL9005
Cooling and FunctionsType of ControllerElectronicType of CoolingVentilatedType of DefrostAutomaticRefrigerantR290Refrigerant Chargeg2x150ThermometerPower and ConsumptionYesEnergy ClassBMax Ambient25°C at 60% RHEnergy ConsumptionkWh/24hPower16 AmpInput PowerW868Voltage / FrequencyV/Hz220-240/50Noise LeveldB(A)Dimensions55Dimension (WxDxH)mmPacked Dimension (WxDxH)mmPacked Dimension (WxDxH)mmAttack2500 x 544 x 1562External Dimension (WxDxH)mm2500 x 544 x 1562	Interior Light		LED
Type of ControllerElectronicType of CoolingVentilatedType of DefrostAutomaticRefrigerantR290Refrigerant Chargeg2x150ThermometerPower and ConsumptionYesEnergy ClassBMax Ambient25°C at 60% RHEnergy ConsumptionkWh/24hAnnual Energy Cons.kWh/yearPower16 AmpInput PowerW868Voltage / FrequencyV/Hz220-240/50Noise LeveldB(A)Dimensions55Dimension (WxDxH)mm2500 x 544 x 1562External Dimension (WxDxH)mmPacked Dimension (WxDxH)mm2650 x 770 x 2320Packed Dimension (WxDxH)mmValue And	Lock		No
Type of Cooling Ventilated Type of Defrost Automatic Refrigerant Charge g 2x150 Thermometer Yes Power and Consumption Energy Class B Max Ambient 25°C at 60% RH Energy Consumption kWh/24h 7,73 Annual Energy Cons. kWh/year 2821 Power 16 Amp Input Power W 868 Voltage / Frequency V/Hz 220-240/50 Noise Level dB(A) 55 Dimensions Internal Dimension (WxDxH) mm 2500 x 544 x 1562 External Dimension (WxDxH) mm 2500 x 740 x 2040 Packed Dimension (WxDxH) mm 2650 x 770 x 2320	Cooling and Functions		
Type of DefrostAutomaticRefrigerantR290Refrigerant Chargeg2x150ThermometerYesPower and ConsumptionEnergy ClassBMax Ambient25°C at 60% RHEnergy ConsumptionkWh/24hEnergy ConsumptionkWh/24hPower16 AmpInput PowerW888Voltage / FrequencyV/Hz220-240/50Noise LeveldB(A)DimensionMxDxH)mm2500 x 544 x 1562External Dimension (WxDxH)mmPacked Dimension (WxDxH)mm250 x 570 x 2320Packed Dimension (WxDxH)mmXatomatic2500 x 570 x 2320Xatomatic <td>Type of Controller</td> <td></td> <td>Electronic</td>	Type of Controller		Electronic
RefrigerantR290Refrigerant Chargeg2x150ThermometerYesPower and ConsumptionEnergy ClassBMax Ambient25°C at 60% RHEnergy ConsumptionkWh/24h7.73Annual Energy Cons.kWh/year2821Power16 AmpInput PowerW868Voltage / FrequencyV/Hz220-240/50Noise LeveldB(A)55DimensionsInternal Dimension (WxDxH)mm2500 x 544 x 1562External Dimension (WxDxH)mm2580 x 740 x 2040Packed Dimension (WxDxH)mm2650 x 770 x 2320	Type of Cooling		Ventilated
Refrigerant Chargeg2x150ThermometerYesPower and ConsumptionYesEnergy ClassBMax Ambient25°C at 60% RHEnergy ConsumptionkWh/24hEnergy ConsumptionkWh/24hAnnual Energy Cons.kWh/yearPower16 AmpInput PowerWKoltage / FrequencyV/HzDimensions2500 x 544 x 1562External Dimension (WxDxH)mmPacked Dimension (WxDxH)mmKuth Construction2500 x 770 x 2320Kuth Construction (WxDxH)mmKuth Construction (WxDxH)Kuth Construction (WxDxH) <t< td=""><td>Type of Defrost</td><td></td><td>Automatic</td></t<>	Type of Defrost		Automatic
ThermometerYesPower and ConsumptionEnergy ClassBMax Ambient25°C at 60% RHEnergy ConsumptionkWh/24hEnergy ConsumptionkWh/24hAnnual Energy Cons.kWh/yearPower16 AmpInput PowerW888Voltage / FrequencyV/Hz220-240/50Noise LeveldB(A)DimensionsInternal Dimension (WxDxH)mm2500 x 544 x 1562External Dimension (WxDxH)mmPacked Dimension (WxDxH)mm2500 x 770 x 2320	Refrigerant		R290
NotePower and ConsumptionEnergy ClassBMax Ambient25°C at 60% RHEnergy ConsumptionkWh/24hEnergy ConsumptionkWh/24hAnnual Energy Cons.kWh/yearPower16 AmpInput PowerW868Voltage / FrequencyV/Hz220-240/50Noise LeveldB(A)5DimensionsInternal Dimension (WxDxH)mm2500 x 544 x 1562External Dimension (WxDxH)mm2580 x 740 x 2040Packed Dimension (WxDxH)mm2650 x 770 x 2320	Refrigerant Charge	g	2x150
Energy ClassBMax Ambient25°C at 60% RHEnergy ConsumptionkWh/24hEnergy ConsumptionkWh/yearAnnual Energy Cons.kWh/yearPower16 AmpInput PowerW868Voltage / FrequencyV/Hz220-240/50Noise LeveldB(A)DimensionsInternal Dimension (WxDxH)mm2500 x 544 x 1562External Dimension (WxDxH)mm2580 x 740 x 2040Packed Dimension (WxDxH)mm2650 x 770 x 2320	Thermometer		Yes
Max Ambient25°C at 60% RHEnergy ConsumptionkWh/24h7.73Annual Energy Cons.kWh/year2821Power16 AmpInput PowerW868Voltage / FrequencyV/Hz220-240/50Noise LeveldB(A)55DimensionsInternal Dimension (WxDxH)mm2500 x 544 x 1562External Dimension (WxDxH)mm2580 x 740 x 2040Packed Dimension (WxDxH)mm2650 x 770 x 2320	Power and Consumption		
Energy ConsumptionkWh/24h7.73Annual Energy Cons.kWh/year2821Power16 AmpInput PowerW868Voltage / FrequencyV/Hz220-240/50Noise LeveldB(A)55DimensionsInternal Dimension (WxDxH)mm2500 x 544 x 1562External Dimension (WxDxH)mm2580 x 740 x 2040Packed Dimension (WxDxH)mm2650 x 770 x 2320	Energy Class		В
Annual Energy Cons. kWh/year 2821 Power 16 Amp Input Power W 868 Voltage / Frequency V/Hz 220-240/50 Noise Level dB(A) 55 Dimensions Internal Dimension (WxDxH) mm 2500 x 544 x 1562 External Dimension (WxDxH) mm 2580 x 740 x 2040 Packed Dimension (WxDxH) mm 2650 x 770 x 2320	Max Ambient		25°C at 60% RH
Power16 AmpInput PowerW868Voltage / FrequencyV/Hz220-240/50Noise LeveldB(A)55DimensionsInternal Dimension (WxDxH)mm2500 x 544 x 1562External Dimension (WxDxH)mm2580 x 740 x 2040Packed Dimension (WxDxH)mm2650 x 770 x 2320	Energy Consumption	kWh/24h	7.73
Input PowerW868Voltage / FrequencyV/Hz220-240/50Noise LeveldB(A)55DimensionsExternal Dimension (WxDxH)mm2500 x 544 x 1562External Dimension (WxDxH)mm2580 x 740 x 2040Packed Dimension (WxDxH)mm2650 x 770 x 2320	Annual Energy Cons.	kWh/year	2821
Voltage / FrequencyV/Hz220-240/50Noise LeveldB(A)55Dimensions55Internal Dimension (WxDxH)mm2500 x 544 x 1562External Dimension (WxDxH)mm2580 x 740 x 2040Packed Dimension (WxDxH)mm2650 x 770 x 2320	Power		16 Amp
Noise Level dB(A) 55 Dimensions Internal Dimension (WxDxH) mm 2500 x 544 x 1562 External Dimension (WxDxH) mm 2580 x 740 x 2040 Packed Dimension (WxDxH) mm 2650 x 770 x 2320	Input Power	W	868
Dimensions Internal Dimension (WxDxH) mm 2500 x 544 x 1562 External Dimension (WxDxH) mm 2580 x 740 x 2040 Packed Dimension (WxDxH) mm 2650 x 770 x 2320	Voltage / Frequency	V/Hz	220-240/50
Internal Dimension (WxDxH)mm2500 x 544 x 1562External Dimension (WxDxH)mm2580 x 740 x 2040Packed Dimension (WxDxH)mm2650 x 770 x 2320Dife Device Dimension (WxDxH)mm2650 x 770 x 2320	Noise Level	dB(A)	55
External Dimension (WxDxH) mm 2580 x 740 x 2040 Packed Dimension (WxDxH) mm 2650 x 770 x 2320	Dimensions		
Packed Dimension (WxDxH) mm 2650 x 770 x 2320	Internal Dimension (WxDxH)	mm	2500 x 544 x 1562
	External Dimension (WxDxH)	mm	2580 x 740 x 2040
40ft Container Load pcs 8	Packed Dimension (WxDxH)	mm	2650 x 770 x 2320
	40ft Container Load	pcs	8



Full height doors

Frameless glass doors