



## GVC38-160 S/S

Vitrine Cooler GN1/3

### Product Features

- Stainless steel lid
- Stainless steel
- Accepts GN1/3 pans (Not supplied)
- Digital controller and temperature display
- Static cooling
- Adjustable feet

### Refrigerated stainless steel topping unit with lid

The GVC is designed to meet the demands of fast-paced food service. Whether you're running a pizzeria, fast-food restaurant, or sandwich shop, this vitrine cooler makes food prep easier, ensuring everything you need is organized and within reach. The topping unit accepts gastronorm pans (not included) – see the technical specifications for more information about the capacity of this specific unit.

The GVC maintains optimal temperatures with a reliable static cooling system. This keeps your ingredients fresh and ready to use, while the manual defrost feature prevents ice build-up for hassle-free operation.

Constructed from durable SS201 stainless steel, the topping shelf is built to last. It is equipped with a stainless steel lid, saving energy and protecting your ingredients. Perfect for businesses where speed and quality are essential, the GVC is designed to optimize your food prep process.

### Measures and Content

|                    |     |             |
|--------------------|-----|-------------|
| Capacity GN Pans   | pcs | 7 x GN1/3   |
| Temperature Range  | °C  | +2 to +8    |
| Net Volume         | l   | 49.7        |
| Gross Volume       | l   | 57.1        |
| Gross / Net Volume | l   | 57.1 / 49.7 |
| Gross / Net Weight | kg  | 55 / 50     |

### Design and Material

|                 |                 |
|-----------------|-----------------|
| Feet / Legs     | Adjustable feet |
| Exterior Finish | SS201           |
| Interior Finish | SS201           |

### Cooling and Functions

|                    |            |    |
|--------------------|------------|----|
| Type of Controller | Electronic |    |
| Type of Cooling    | Static     |    |
| Type of Defrost    | Manual     |    |
| Refrigerant        | R600a      |    |
| Refrigerant Charge | g          | 45 |
| Thermometer        | Yes        |    |

### Power and Consumption

|                     |          |               |
|---------------------|----------|---------------|
| Max Ambient         |          | +30°C, 55% RH |
| Annual Energy Cons. | kWh/year | 964           |
| Energy Consumption  | kWh/24h  | 2.64          |
| Power Supply        |          | 13 Amp        |
| Input Power         | W        | 110           |
| Voltage / Frequency | V/Hz     | 220-240/50    |
| Noise Level         | dB(A)    | 40            |

### Dimensions

|                            |     |                    |
|----------------------------|-----|--------------------|
| External Dimension (WxDxH) | mm  | 1600 x 395 x 288.5 |
| Internal Dimension (WxDxH) | mm  | 1250 x 305 x 150   |
| Packed Dimension (WxDxH)   | mm  | 1700 x 435 x 330   |
| 40ft Container Load        | pcs | 210                |



Accepts GN1/3 pan(s) (not supplied)



Stainless steel lid for protection of food